PRODUCT DATA SHEET

wellTEC® Profile SW-48/100-45/60-18/76









TECHNICAL DETAILS

WIDTHS:

Different widths depending on the compilation of the waves.

MOUNTING:

Visible

Connection profiles or sheet material can be supplied on demand.

MATERIALS:

Aluminum (AW-5005) mill finished, normal quality or anodising quality
Aluminum (AW-3005) coil coated on one side
Also available in steel, stainless steel, zinc, copper, brass

THICKNESSES:

1.0 mm

LENGTHS:


Up to 5,500 mm

PERFORATIONS ACCORDING TO DIN 24041:

Round holes in staggered rows Rv-2/3.5 approx. 29.62% Round holes in staggered rows Rv-3/5 approx. 32.65% Round holes in staggered rows Rv-4/6 approx. 40.31% Round holes in staggered rows Rv-5/8 approx. 35.43%

The concrete details and tolerances for your order can be found in our order-related release drawings.

EXAMPLE OF PROFILE CROSS SECTION:



GET IN TOUCH WITH US:

MN Metall GmbH

Industrieweg 34 Tel. +49 (0) 4561/51 79-0 E-mail: info@mn-metall.de D-23730 Neustadt Fax +49 (0) 4561/51 79-35 Internet: www.mn-metall.de

MN Metall GmbH – since 1974 the specialist for innovative sheet metal work. We give shape to your ideas!